

PERSONAL WATERCRAFT DOCKING PLATFORM

RECOMMENDED FOR

- One-, two- and three-place PWCs
- Floating or fixed docks
- Front- or side-mount installations

TECHNICAL SPECS

- 12' 6" overall length
- 15" overall depth
- 4' 10" overall width
- Total weight 270 lbs
- Max. working load capacity 1625 lbs



- Universal mount for floating or fixed docks (pictured with optional heavy-duty brackets)

- Rigid Mount Hardware for Floating docks



© 2014 HYDROHOIST MARINE GROUP
HYDROPORT²XL 01/14



Your authorized **HydroHoist**[®] dealer is:

HydroHoist[®]
MARINE GROUP

HydroHoist Boat Lifts • HyPower • Rotek

CORPORATE OFFICE
915 West Blue Starr Drive
Claremore, OK 74017 USA

(918) 341-6811 • 1-800-825-3379 (U.S.)

sales1@boatlift.com • boatlift.com

HYDROPORT²XL[™]

PERSONAL WATERCRAFT DOCKING PLATFORM



HydroHoist[®]
BOAT LIFTS

800.825.3379 • BOATLIFT.COM

HYDROPORT²XL™

PERSONAL WATERCRAFT DOCKING PLATFORM



Protect your craft and enjoy fast, convenient access to the water with the **HydroPort2XL™** PWC Docking Platform. It features an exclusive bow bumper that slows your craft's forward motion and provides a soft rest for the keel. A tapered entry with dual bow rollers help center your craft. In-line rollers make launching easy and convenient.

The **HydroPort2XL™** can be front or side-mounted on floating or fixed docks. A molded-in tie-down loop is provided at the bow to secure your craft. An optional connecting link locks multiple units together.

STANDARD FEATURES

- Ultra-tough polyethylene construction
- In-line roller wheel design
- Two docking platforms per 10 ft. slip
- Exclusive patented bow bumper
- Molded-in tie-down loop
- Front- or side-mount mooring hardware
- Universal hull support
- Mounting hardware for both fixed and floating docks
- Available in tan and blue



- Connecting hardware to link multiple front-mounted units together



DRIVE ON TO DOCK



ROLL OFF TO LAUNCH