

Why Should You Own a HydroHoist® Boat Lift?

Simply put, **it's the best and most engineered boat lift in the industry** — with the highest resale value.

LOW MAINTENANCE

- Keeps hull clean
- Prevents marine growth from accumulating on outdrives
- Hull can easily be sprayed off and wiped down when on lift
- Keeps your boat looking new for years to come

PROTECT YOUR INVESTMENT

- Prevents boat from hitting dock during heavy wake or inclement weather
- Controls water osmosis in hull of boat
- Protects boat and outdrives from electrolysis

READY TO GO

- Immediate access to the water
- Far superior to trailering or dry stack storage



Marine Accessories

BOW GUIDE



CORNER BUMPERS



HYDROFENDER™



ULTRAFENDER™



PLANK KIT



HYDRO LOCKER™



Your authorized **HydroHoist®** dealer is:

HARBORHBO20 ©2019 HYDROHOIST | 11-19

HPTM SERIES

HYDROPORT® PWC Docking Platforms

HP Pro®

HP Extreme®

HP EPIC®



- Easily adjustable 5" x 2" rollers to accommodate all models of watercraft
- Ultra-tough polyethylene plastic with (EPS) marine foam — for increased strength and leak elimination*
- Front or side-mount capability for fixed or floating docks
- Up to 2,000 lb. capacity

*Available on certain models

HydroHoist®
Boat Lifts • HyPower • RotoMoldUSA

915 West Blue Starr Dr. | Claremore, OK 74017
(800) 825-3379 • Boatlift.com
sales1@boatlift.com

WE MAKE BOATING EASY!

HarborHoist™

BOATLIFT.COM



4,400-25,000



FREE FLOATING

QUICK OPERATION

LEVEL-LIFTING



HydroHoist®
BOAT LIFTS

HARBORHOIST™ VERSATILITY




***HarborHoist™** has a level-lifting frame constructed of high-strength grade aluminum. The most versatile boat lift in the HydroHoist family — perfect for fresh and salt water.*

HarborHoist is compatible with fixed or floating docks, and works in a U-shaped slip, double-wide slip, L-shaped Finger Pier dock, and square dock. The hull supports can be configured for nearly all boat styles, including inboard, wake, pontoon, and tritoon boats.

The unit can simply be tied to the dock or use a conventional mooring system. HarborHoist comes standard with a push button control unit. Walkways are mounted to the top of the tanks that run the full length of the lift for easy access to your boat in both the up or down position.

STANDARD FEATURES

- Most versatile, free-floating lift
- Rugged, marine-grade polyethylene tanks
- Continuous walkways full length of the lift for safety and easy access
- Aluminum structure to extend the life of the product
- Push button control mounted directly on the lift
- Level-lifting operation
- Quick lift and launch operation
- Adjustable hull pads
- Easy loading and unloading of passengers
- Simple assembly and installation



HarborHoist™ can simply be tied to the dock. Additional mooring kit options are available.

STRUCTURAL SPECIFICATIONS

Capacity	No. of Floats	Overall Length	Min. Width	Beam of Boat	Water Depth Required
4,400 Lbs 1,995 kg	4	14'-2" / 4.31m	11' / 3.35m	Up to 9' 6" / 2.74m	24" / .609m + Draft
6,600 Lbs 2,993 kg	6	16'-10" / 5.13m	11' / 3.35m	Up to 9' 6" / 2.74m	24" / .609m + Draft
8,800 Lbs 3,991 kg	8	22'-6" / 6.85m	11' / 3.35m	Up to 9' 6" / 2.74m	24" / .609m + Draft
8,800 Lbs SHORT* 4,082 kg	6 plus 1-Aux. (24"/.609m depth)	16'-10" / 5.13m	12' / 3.65m	Up to 9' 6" / 2.74m	31" / .787m + Draft
12,000 Lbs 5,443 kg	8 plus 1-Aux. (36"/.914m depth)	22'-6" / 6.85m	12.5' / 3.81m	9' 6" to 11' 6" 2.89m to 3.50m	43" / 1.09m + Draft
12,000 Lbs Shallow Water 5,443 kg	8 plus 1-Aux. (24"/.609m depth)	22'-6" / 6.85m	12.5' / 3.81m	9' 6" to 11' 6" 2.89m to 3.50m	31" / .787m + Draft
15,000 Lbs 6,803 kg	8 plus 2-Aux. (36"/.914m depth)	22'-6" / 6.85m	12.5' / 3.81m	9' 6" to 11' 6" 2.89m to 3.50m	43" / 1.09m + Draft
15,000 Lbs Shallow Water 6,803 kg	8 plus 2-Aux. (24"/.609m depth)	22'-6" / 6.85m	12.5' / 3.81m	9' 6" to 11' 6" 2.89m to 3.50m	31" / .787m + Draft
18,000 Lbs 8,164 kg	8 plus 2-Aux.	22'-6" / 6.85m	13' / 3.96m	9' 6" to 12' 0" 2.89m to 3.65m	43" / 1.09m + Draft
20,000 Lbs 9,071 kg	10 + 2 Aux. (48" Wide)	28'-2" / 8.58m	13' / 3.96m	9' 6" to 12' 0" 2.89m to 3.65m	43" / 1.09m + Draft
20,000 Lbs W 9,071 kg W	10 + 2 Aux. (48" Wide)	28'-2" / 8.58m	14' 7" / 4.44m	9' 6" to 13' 6" 2.89m to 4.11m	43" / 1.09m + Draft
25,000 Lbs 11,339 kg	10 + 3 Aux. (48" Wide)	28'-2" / 8.58m	13' / 3.96m	9' 6" to 12' 0" 2.89m to 3.65m	43" / 1.09m + Draft
25,000 Lbs W 11,339 kg W	10 + 3 Aux. (48" Wide)	28'-2" / 8.58m	14' 7" / 4.44m	9' 6" to 13' 6" 2.89m to 4.11m	43" / 1.09m + Draft

Overall Width for all models: 34" + Beam / 0.863m **Volts/Amps for all models:** 110V/15A

*For boats 28' and under

Note: Aluminum pads standard on all capacities; wood hull pads for pontoon and tritoon only.



sales1@boatlift.com

BOATLIFT.COM